

RIGHT-angled triangle

ALPINE CHEMICAL PRODUCTS

31458

Fig. 1

STREET ADDRESS: 1824 S.W. 352nd. PLACE CITY, STATE, ZIP CODE: FEDERAL WAY, WA
98023

INFORMATION TELEPHONE NO.: 206-838-4318 EMERGENCY TELEPHONE NO.: SAME

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: Waterless Cleaner

PRODUCT CLASS: Solvent

PRODUCT(S) NUMBER(S)

SECTION II - HAZARDOUS INGREDIENTS

NE = NOT ESTABLISHED

NA = NOT APPLICABLE

NK = NOT KNOWN

BOTTLED RANGE: 315-355°F

WEIGHS DENSITY: X HEAVIER LIGHTER THAN AIR

EVAPORATION RATE: ____FASTER SLOWER THAN ETHER % VOLATILE
BY VOLUME: 100 WEIGHT PER GALLON: 6.5 lbs.

APPEARANCE AND ODOR: Water clear with solvent odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA Combustible Liquid - Class III

DOE: Combustible Liquid

FLASH POINT: 104°F

LEI: 9.7

EXTINGUISHING MEDIA: Regular foam, carbon dioxide, water fog or dry chemical.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Keep away from heat, sparks, and open flame. Closed containers may explode (due to build-up of steam pressure) when exposed to extreme heat.

SPECIAL FIREFIGHTING PROCEDURES: Self-contained breathing apparatus with full face piece operated under positive pressure. Water may be used to cool containers to prevent pressure build-up and possible explosion when exposed to extreme heat.

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL - See Section II

THRESHOLD LIMIT VALUE - See Section II

31458

Pg. 2

EFFECTS OF OVEREXPOSURE: Acute: Eyes: Can cause severe irritation, redness, tearing, blurred vision. Skin: Prolonged or repeated contact can cause moderate irritation and dermatitis. Breathing: Can cause nasal and respiratory irritation, dizziness, and nausea. Aspiration into the lungs can cause chemical pneumonitis, which can be fatal. Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal.

CHRONIC EXPOSURE: Solvents have been reported to cause permanent brain and nervous system damage with possible liver and kidney damage. Respiratory and skin sensitization.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Dermatitis, allergic responses, diseases of skin and lungs.

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES: Skin: Wash with soap and water. Eyes: Flush immediately with water for 15 minutes, get medical attention immediately. Inhalation: If affected by vapors or spray mist, remove to fresh air. If in a coma or breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. In either case get medical attention immediately. Keep person warm and quiet. Ingestion: Do not induce vomiting, get medical attention immediately.

Remove contaminated clothing and shoes.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE STABLE

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, various hydrocarbon compounds.

CONDITIONS TO AVOID: High temperatures, hot surfaces, electric arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents (e.g. nitric acid, permanganates, etc.).

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spill. Soak up with rags, sand, flour absorbent. Eliminate all sources of ignition (flame, sparks, etc.), exclude from area persons without protective equipment. Use non-sparking tools.

31458

WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State and local regulations. Use licensed hazardous waste disposal company.

Pg.3

SECTION VIII - S A F E H A N D L I N G A N D U S E I N F O R M A T I O N

RESPIRATORY PROTECTION: If PEL or TLV is exceeded, use NIOSH/MSHA respirator TC23C or equivalent.

VENTILATION: Provide sufficient mechanical and/or local exhaust ventilation to maintain exposure below PEL or TLV. Follow OSHA 29CFR part 1910.94.

PROTECTIVE GLOVES: Neoprene or Nitrile Rubber

EYE PROTECTION: Safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: To prevent repeated or prolonged contact, wear impervious clothing and boots. Use protective cream if skin contact is likely.

HYGENIC PRACTICES: Wash hands before eating or smoking. Do not consume food or beverage while using this product.

SECTION IX - S P E C I A L P R E C A U T I O N S

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store away from heat, sparks, and flame. Keep containers tightly closed.

OTHER PRECAUTIONS: Do not reuse container. Empty containers may contain hazardous residue. Keep away from heat, sparks and flame. Do not cut, puncture or weld on or near container. Prevent breathing of vapor or spray mist.

The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with manufacturer or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their