Material Safety Data Sheet

NOVASEAL CONCRETE

OF 4 PAGES

31480

Section 1. Chemical product and company identification

Trade name

: NOVASEAL CONCRETE

Product use

: Floor care product

Supplier

Ecolab Inc.

370 N. Wabasha St. St. Paul. MN 55102

1-800-352-5326

Code

920763

Date of issue

: 01-September-2006

EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	% by weight
2-(2-butoxyethoxy)ethanol	112-34-5	2
ethanediol	107-21-1	2
dipropylene glycol methyl ether	34590-94-8	1 - 5
3-butoxypropan-2-ol	5131-66-8	1 - 5

Section 3. Hazards identification

Physical state

: Liquid. (Liquid.)

Emergency

: CAUTION!

overview

MAY CAUSE EYE AND SKIN IRRITATION.

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Potential acute health effects

Eyes

: Moderately irritating to eyes.

Skin

: Moderately irritating to the skin.

Inhalation Ingestion

: No known significant effects or critical hazards. : No known significant effects or critical hazards.

See toxicological information (section 11)

Section 4. First aid measures

Eye contact

: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention if irritation persists.

Skin contact

: Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Get medical attention if irritation persists. Remove contaminated clothing and shoes. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

: If inhaled, remove to fresh air.

Ingestion

: Do not induce vomiting. Never give anything by mouth to an unconscious person. If irritation persists, get medical attention.

Section 5. Fire fighting measures

Flash point

: 93.3333 °C (Closed cup)

Fire-fighting media and

: Use an extinguishing agent suitable for the surrounding fire.

instructions

Dike liquid for later disposal.

No specific hazard.

Special protective equipment:

for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

Section 6. Accidental release measures

#31480

Personal precautions

: Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.

Environmental precautions Methods for cleaning up

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling

: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage

: Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.

Do not store below 0°C

Section 8. Exposure controls, personal protection

Engineering controls

: Good general ventilation should be sufficient to control airborne levels.

Personal protection

Eyes

: Eye protection recommended.

Hands

: For prolonged or repeated handling, use the following type of gloves: Impervious gloves.

Skin

: No protective equipment is needed under normal use conditions.

Respiratory

: A respirator is not needed under normal and intended conditions of product use.

<u>Name</u>

Exposure limits

dipropylene glycol methyl ether

ACGIH TLV (United States, 1/2005). Skin STEL: 909 mg/m³ 15 minute/minutes. Form: All forms STEL: 150 ppm 15 minute/minutes. Form: All forms TWA: 606 mg/m³ 8 hour(s). Form: All forms

TWA: 100 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997). Skin

TWA: 600 mg/m³ 8 hour(s). Form: All forms

TWA: 100 ppm 8 hour(s). Form: All forms

ACGIH TLV (United States, 1/2005).

ethanediol

CEIL: 100 mg/m³ Form: Aerosol

Section 9. Physical and chemical properties

Physical state

: Liquid. (Liquid.)

Color

: opaque

Odor Ha : Faint odor. : 7.65 (100%)

Boiling/condensation

: >100 °C

point

Specific gravity

: 1.02 (Water = 1)

Solubility

: Easily soluble in cold water, hot water.

Section 10. Stability and reactivity

Stability

: The product is stable.

NOVASEAL CONCRETE Page: 3/4 Section 11. Toxicological information Potential acute health effects #31480

Ingestion : No known significant effects or critical hazards. Potential chronic health effects

Chronic effects on humans

Eyes

Skin

Inhalation

: Classified Reproductive system/toxin/female, Reproductive system/toxin/male,

Development toxin [POSSIBLE] [ethanediol].

: No known significant effects or critical hazards.

: Moderately irritating to eyes.

: Moderately irritating to the skin.

Contains material which causes damage to the following organs: kidneys, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Contains material which may cause damage to the following organs: the reproductive

system.

Section 12. Ecological information

Products of degradation

: These products are carbon oxides (CO, CO₂) and water.

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information		Proper shipping name		group	Additional information
DOT Classification	Not regulated.	-	-	TO THE SEPTEMBERS OF THE SEPTE	Not available.

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classificătion

: Irritating material

Target organ effects

U.S. Federal regulations

SARA 302/304/311/312 extremely hazardous substances: No products were

SARA 302/304 emergency planning and notification: No products were found.

TSCA 8(b) inventory

: All materials are listed or exempt.

SARA 313

Product name

Concentration 1.79

Form R - Reporting requirements: 2-(2-butoxyethoxy)ethanol

ethanediol


1.5215

California Prop. 65 : No products were found.

Section 16. Other information

Hazardous Material

Information System (U.S.A.)



Date of issue

01-September-2006.

NOVASEAL CONCRETE

Page: 4/4

Responsible name

Date of previous issue

: Regulatory Affairs

: No previous validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.