31673+31674 pg.10f2

NFPA: H = 3, F = 0, R = 0

HMIS Rating: Health = 3 Startes and the startes are the startes and the startes are the startes are

MIS Rating	g: Health = 3 . Flammability = 0. Reactivity	<u>= 0. </u>	・ \ → >
ECTION	I - IDENTITY AND MANUFACTU	RER'S INFORMATION (04	90B)
Aanufacture Iame	r's HILLYARD INDUSTRIES	Product RENOVATO	DR
ddress	302 North Fourth Street	Date	

Prepared by Regulatory Atlairs Department Prepared by Regulatory Atlairs Prepared by Regulatory Atlairs Prepared by Regulatory Atlairs Prepared by Regulatory Atlairs Prepared by Regulatory Prepared by Regul	Address 302 North Fourth Street St. Joseph, MO 64502	D	ate	5 1001		····-		
Components (Specific Chemical Identity, Common Name(s)) Ethanolamine (1) (nuisance 6834-92-0 2 mg/M³ 2 mg/M³ N/A 4-6 Sodium metasilicate (2) dust 7. Nater 7.732-18-5 none none N/A Benizyl alcohol (3) 100-51-6 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A Sulfonated by OSHA, CT, FL, JL, LA, MA, NJ, PA, RI (1) Regulated by OSHA, CT, FL, JL, LA, MA, NJ, PA, RI (2) Regulated by PA (RTK), FL, MA Common My		may 10, 1331						
Components (Specific Chemical Identity, Common Name(s)) Ethanolamine (1) (nuisance 6834-92-0 2 mg/M³ 2 mg/M³ N/A 4-6 Sodium metasilicate (2) dust 7. Nater 7.732-18-5 none none N/A Benizyl alcohol (3) 100-51-6 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A Sulfonated by OSHA, CT, FL, JL, LA, MA, NJ, PA, RI (1) Regulated by OSHA, CT, FL, JL, LA, MA, NJ, PA, RI (2) Regulated by PA (RTK), FL, MA Common My	Emergency Telephone No.: CHEMTREC (800) 4:	24-9300 (Only in the ever	nt of chemical emerge	ncy involving a si	oill leak fire	exposure or accident		
Components (Specific Chemical Identity, Common Name(s)) Ethanolamine (1) (nuisance 141-43-5 3 ppm 3 ppm N/A 4-6 Sodium metasilicate (2) (dust) 6834-92-0 2 mg/M³ 2 mg/M³ N/A 5-10 Mater 7732-18-5 none none N/A Benzyl alcohol (3) 100-51-6 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A Salt (1) Regulated by OSHA, CT, FL, IL, LA, MA, NI, PA, RI (2) Regulated by PA (RTK), FL, MA SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity(H20=1) 356°C 1.08 Vapor Pressure (mm H3) at 20°C 17.1 By Volume (%) average 90.8 Vapor Density (Air = 1) Solubility in Water appreciable Appearance and Other appreciable Appearance and Other appreciable Appearance and Other appreciable Limits LEL N/A UEL N/A Water and Carbon Hysical Hazards What is a special Fire Fighting Procedures N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Section V — PHYSICAL HAZARDS	involving chemicals.)		Other	Information Call	s (816) 2:	33-1321 (Ext. 303)		
Ethanolamine (1)					Other Limit			
Sodium metasilicate (2) (dust) 6834-92-0 2 mg/M³ 2 mg/M³ N/A 5-10 Water 7732-18-5 none none N/A Benzyl alcohol (3) 100-51-6 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A salt (1) Regulated by OSHA, CT. FL. JL. LA. MA, NJ. PA, RI (2) Regulated by OSHA, CT. FL. JL. LA. MA, NJ. PA, RI (3) Regulated by PA (RTK), FL, MA SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O=1) 53°C 1.05°C Vapor Pressure (mm Hg) at 20°C 17.1 By Volume (%) average 90.8 Vapor Density (Air=1) 0.7 Evaporation Rate 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				ACGIH TLV				
Nater 7732-18-5 none none N/A	(nui sa	ince						
Benzyl alcohol (3) 100-51-6 none none N/A Sulfonated oleic acid, potassium 68609-93-8 none none N/A salt (1) Regulated by OSHA, CT, FL, IL, LA, MA, NJ, PA, RI (2) Regulated by OSHA (3) Regulated by PA (RTK), FL, MA (3) Regulated by PA (RTK), FL, MA (4) Regulated by PA (RTK), FL, MA (5) Regulated by PA (RTK), FL, MA (6) Regulated by PA (RTK), FL, MA (7) Regulated by PA (RTK), FL, MA (8) Regulated by PA (RTK), FL, MA (9) Regulated by PA (RTK), FL, MA (9) Regulated by PA (RTK), FL, MA (10) Regulated by PA (RTK), FL, MA (11) Regulated by PA (RTK), FL, MA (12) Regulated by PA (RTK), FL, MA (13) Regulated by PA (RTK), FL, MA (14) Regulated by PA (RTK), FL, MA (15) Regulated by PA (RTK), FL, MA (16) Regulated by PA (RTK), FL, MA (17) Regulated by PA (RTK), FL, MA (18) Regulated by PA (RTK), FL, MA (19) Regulated by PA (RTK), FL, MA (19) Regulated by PA (RTK), FL, MA (10) Regulated by PA (RTK), FL, MA (11) Regulated by PA (RTK), FL, MA (12) Regulated by PA (RTK), FL, MA (13) Regulated by PA (RTK), FL, MA (14) Regulated by PA (RTK), FL, MA (15) Regulated by PA (RTK), FL, MA (16) Regulated by PA (RTK), FL, MA, NJ, PA, RI (17) Regulated by PA (RTK), FL, MA (18) Regulated by PA (RTK), FL, MA, NJ, PA, RI (18) Regulated by PA (RTK), FL, MA, NJ, PA, RI (19) Regulated by PA (RTK), FL, MA, NJ, PA, RI (10) Regulated by PA (RTK), FL, MA, NJ, PA, RI (10) Regulated by PA (RTK), FL, MA, NJ, PA, RI (10) Regulated by PA (RTK), FL, MA, NJ, PA, RI (11) Regulated by PA (RTK), FL, MA, NJ, PA, RI (12) Regulated by PA (RTK), FL, MA, NJ, PA, RI (13) Regulated by PA (RTK), FL, MA, NJ, PA, RI (14) Regulated by PA (RTK), PA, RI (15) Regulated by PA (RTK), PA, RI (16) Regulated by PA (RTK), PA, RI (17) Regulated by PA (RTK), PA, RI (18) Regulated	Sodium metasilicate (2) 'dust)	6834-92-	_	2 mg/M ³		5-10		
Sulfonated oleic acid, potassium 68609-93-8 none none N/A								
(1) Regulated by OSHA, CT, FL, JL, LA, MA, NJ, PA, RI (2) Regulated by OSHA (3) Regulated by PA (RTK), FL, MA SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 250°C 1.05 Vapor Pressure (mm Hs.) at 20°C 17.1 Percent Volarite By Volume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate 10.5 Solubility in Water 0.7 Appearance and Odor 2010 Appeara					· · · · · · · · · · · · · · · · · · ·			
(2) Regulated by OSHA (3) Regulated by PA (RTK), FL, MA SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1:05 Vapor Pressure (mm Hg.) at 20°C 17.1 By Volume (%) average 90.8 Vapor Obensity (Mir = 1) 0.7 Evaporation Rate Evaporation Rate (paper and Odor suppreciable violet liquid: non-objectionable odor setting Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A Incompassibility (Waterials to Avoid) N/A Incompassibility (Physical Conditions Products Or Payoreducts Or Payore		1.Wii 68609-93-	8 none	none	N/A			
(2) Regulated by OSHA (3) Regulated by PA (RTK), FL, MA SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1:05 Vapor Pressure (mm Hg.) at 20°C 17.1 By Volume (%) average 90.8 Vapor Obensity (Mir = 1) 0.7 Evaporation Rate Evaporation Rate (paper and Odor suppreciable violet liquid: non-objectionable odor setting Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Data Conditions N/A Incompassibility (Waterials to Avoid) N/A Incompassibility (Physical Conditions Products Or Payoreducts Or Payore								
(2) Regulated by OSHA (3) Regulated by PA (RTK), FL, MA SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1.05 Vapor Pressure (mm Hg) at 20°C 17.1 Percent Volatife syrotume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate 1 that 1 the syrotume (%) appreciable violet liquid; non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) Flammable Limits LEL N/A UEL N/A Extinguishing Media Mater, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A SECTION V — PHYSICAL HAZARDS Stability Unstable D Conditions N/A Incompassibility (Materials to Avoid) N/A Incompassibility (Materials to Avoid) N/A Incompassibility (Materials to Avoid) Products (Cr. Marchael Conditions) Products (Cr. Marchael Cr. Ma	(1) Regulated by OSHA, CT. FL.	TI. I.A MA NI	PA DT					
SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1:05 Vapor Pressure (mm Hs.) at 20°C 17.1 Percent Volatile Ry Volume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate athylether = 1) less than 1 Appearance and Odor Appearance and Odor Violet 1 input; non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) Flammable Limits LEL N/A UEL N/A Extraguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire and Explosion Hazards N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable 10 Conditions Stable 10 to Avoid N/A Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Ox By proreducts N/A Oxidizing materials Hazardous Decomposition Products Ox By proreducts		-	•					
SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1.05 Vapor Pressure (mm Hs.) at 20°C 17.1 Percent Volatile By Volume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate = 1) less than 1 Solubility in Water appreciable Violet liquid: non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) Flammable Limits LEL N/A Extraguishing Media Water fry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stebility Unstable 0 Conditions N/A Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Of Porrorducts								
SECTION III — PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point 745 mm Hg 211°F Specific Gravity (H ₂ O = 1) 35°C 1:05 Vapor Pressure (mm Hg.) at 20°C 17.1 Percent Volatile By Volume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate athyl other = 1) less than 1 Solubility in Water Appearance and Odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) Flammable Limits LEL N/A Extinguishing Media Water Ary chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable Conditions Stable 10 Conditions Stable 10 Conditions Stable 12 Conditions Stable 13 Conditions Stable 13 Conditions Stable 13 Conditions Stable 14 Conditions Stable 15 Conditions Stable 15 Conditions Stable 15 Conditions Stable 15 Conditions Stable 16 Conditions Stable 17 Conditions Stable 17 Conditions Stable 18 Con						į		
Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1.05 Vapor Pressure (mm Hs.) at 20°C 17.1 Percent Volatile Sy Volume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate appreciable violet liquid: non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) none to holling (T.C.C.) Flammable Limits LEL N/A UEL N/A Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable D Conditions Stable D Conditions to Avoid N/A Incompatibility (Materials to Avoid) (Oxidizing materials Hazardous Decomposition Products Of Revorducts Supercials Conditions Condition								
Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1.05 Vapor Pressure (mm Hs.) at 20°C 17.1 Percent Volatile Sy Volume (%) average 90.8 Vapor Density (Air = 1) 0.7 Evaporation Rate appreciable violet liquid: non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) none to holling (T.C.C.) Flammable Limits LEL N/A UEL N/A Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable D Conditions Stable D Conditions to Avoid N/A Incompatibility (Materials to Avoid) (Oxidizing materials Hazardous Decomposition Products Of Revorducts Supercials Conditions Condition	<u> </u>	······································						
Boiling Point 745 mm Hg 211°F Specific Gravity (H2O = 1) 25°C 1.05 Vapor Pressure (mm Hg.) at 20°C 17.1 Percent Volatile By Volume (%) average 90.8 Vapor Density (Air = 1) Solubility in Water 0.7 (paperance and Odor violet Liquid: non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) none to halling (T.C.C.) Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable D Conditions Stable D Conditions	·		···					
Vapor Pressure (mm Hg.) at 20°C 17.1 By Volume (%) By Volume (%) Apperance and Odor Appreciable Violet liquid, non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) None to holiling (T.C.C.) Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable	**************************************	CAL CHARACTERIS			2500			
Vapor Density (Air = 1) Vapor Density (Air = 1) O.7 Solubility in Water Section IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) none to holiling (T.C.C.) Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A Section V — PHYSICAL HAZARDS Stability Unstable D Conditions Stable D Conditions Stable D Conditions (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Byproducts	745 mm H	g 211°F		O = 1)	25°C 39°C	1:85		
Solubility in Water Solubility in Water SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) None to hoiling (T.C.C.) Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable	at 20°C	17.1			average	90.8		
Appreciable violet liquid: non-objectionable odor SECTION IV — FIRE AND EXPLOSION HAZARD DATA Flash Point (Method Used) None to hoiling (T.C.C.) Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable D Conditions Stable D to Avoid N/A Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Bororducts Hazardous Decomposition Products Or Bororducts	Vapor Density (Air = 1)	0.7		thyl ether	<u> </u>	less than 1		
Flash Point (Method Used) none to hoiling (T.C.C.) Exinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable	Solubility in Water	appreciable			ectionah	le odor		
none to hoiling (T.C.C.) Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable	SECTION IV — FIRE AND EXPLOSI							
Extinguishing Media Water, dry chemical, alcohol foam or carbon dioxide Special Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable			Flammable Limits	LEL	/A	UEL N/A		
Unusual Fire Fighting Procedures N/A Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable	Extragriching Media	foam or carbon d	lioxide					
Unusual Fire and Explosion Hazards N/A SECTION V — PHYSICAL HAZARDS Stability Unstable	Special Fire Fighting Procedures							
SECTION V — PHYSICAL HAZARDS Stability Unstable D Conditions Stable 10 to Avoid N/A Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Byproducts	MA			· · · · · · · · · · · · · · · · · · ·				
SECTION V — PHYSICAL HAZARDS Stability Unstable					•			
Stability Unstable Conditions Stable to Avoid N/A Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Byproducts	N/ A							
Stability Unstable Conditions Stable to Avoid N/A Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Byproducts	SECTION V - PHYSICAL HAZARD					.,		
Incompatibility (Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Byproducts	Stability Unstable II Conditions	<u> </u>				······································		
(Materials to Avoid) Oxidizing materials Hazardous Decomposition Products Or Bygroducts								
Hazardous Decomposition Products Or Byproducts	(Materials to Avoid)			·	•			
Products Or Byproducts None known to manufacturer	Hazardous Decomposition		·					
	Products Or Byproducts None known to manufacturer					•		
Hazardous May Occur © Conditions Polymerization Will Not Occur © To Avoid N/A				· .		<u> </u>		

	ATAI			01/77 . 3	237 - 231
#120, Renovator				31673 03	01679
SECTION VI - HEALT	H HAZARD DATA			17.0	5/16/91
Route(s) of Entry:	Inhalation?	Skin?		Ingestion?	3/ 10/ 31
Health Hazards (1. Acute and	yes yes	yes		yes	
1. Concentrate is	corrosive to all body	tissue with wh	ich it comes	in contact.	
	epeated exposure to the			tis. Inhalatio	n of
spray mist may res	ult in varying degrees	of irritation	, i.		
Chemical Listed as Carcinogo or Potential Carcinogen		D 1.A.R.C. Monographs	Yes D	OSHA Yes D No R	
	sure act may produce skin a of the mouth, throat;			produce burns	of
Medical Conditions Generally Aggravated by Exp Skin problems such	osure as industrial dermat	itis.	•		
with water again. contaminated shoes	immediately flush ey ig contaminated clothing contaminated clothing is. If swallowed do not expressed air; if respirat	. Wash clothing induce vomiting	<u>y before reus</u> ng: immediate	e and thorough ly give large	nly clean amounts of
SECTION VII — PREC	CAUTIONS FOR SAFE HAI	NDLING AND US			
Wear/use appropria	Material is Released Or Spilled ate protective equipme bent material and place ith water. Large spill	nt Small spil e into contain s: Dike far ah	ls: Take up weers for later ead of liquid	vith wet vac. I disposal. Ri spill for la	nop or non- nse affected ter pick-up
at a permitted far waste - pH conc.	ntrate regulated by Fe 40 CFR 261.22). Dispos cility in accordance w = 13-14). Waste from r n compliance with appl	<u>vith federal/st</u> normal product	<u>ate/local reg</u> use may be se	<u>ulations (cor</u> wered to publ	rosive ic-owned
Precautions To Be Taken In Keep container cl	Handling And Storing osed when not in use.		-	-	ments
for recycling or	reconditioning.				
	oduce respiratory irri			roper ventilat	ion. Do not
	sprayer without respi	ratory protect	10n. *		
SECTION VIII — CO					
Respiratory Protection (Spe Ventilate to keep	cify Type) air below TLV on meta	asilicate and m	onoethanolam	ine.	
Ventilation	Local Med	chanical	Special	Other	

N/A recommended recommended N/A

Eye Protection chemical safety goggles when working with conc. Protective Gloves impervious gloves when working with conc.

Other Protective Clothing Or Equipment impervious to water and alkaline liquids where contact with conc. is a concern

Work/Hygienic Practices Wash thoroughly after handling

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE. MISUSE OR DISPOSAL OF THESE PRODUCTS.

* This product contains no reportable quantities of toxic chemicals subject to reporting requirements of Sec. 313 of SARA Title III Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR Part 372.