3177

MATERIAL SAFETY DATA SHEET

Complies with OSHA's 29 CFR 1910.1200 and State Hazard Communication Standards

ICL Division of Rochester Midland 1015 North 14 Street Omaha, NE 68102 (402) 342-4248

Medical Emergency Telephone (716) 266-2283

SECTION 1

PRODUCT IDENTITY: ARISTO SUPREME Gym Finish

DATE PREPARED: 6/24/93

NFPA/HMIS HAZARDS CODES: (minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 2/2 Fire: 2/2 Reactivity: 0/0 Personal Protection: 2/2

SECTION 2: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTSCAS #OSHA-PELACGIH-TLV% BY WT.ResinsNot Est.Not Est.Not Est.40

Stoddard Solvent 64741-41-9 Not Est. 100 ppm(TWA) 60

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 320°F SPECIFIC GRAVITY: 0.875

VAPOR PRESSURE: Not applicable PERCENT VOLATILE: 60

VAPOR DENSITY (air=1): > 1 EVAPORATION RATE: (ethyl ether=1) >1

SOLUBILITY IN WATER: Negligible pH: Not applicable

MELTING POINT: Not applicable

APPEARANCE AND ODOR: Viscous amber liquid with mineral spirit odor

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 103°F (TCC) FLAMMABLE LIMITS: Not applicable

EXTINGUISHING MEDIA: Foam, Dry chemical CO,

SPECIAL FIREFIGHTING PROCEDURES: Water will be ineffective UNUSUAL FIRE AND EXPLOSION HAZARDS: Spray front to back

SECTION 5: REACTIVITY DATA

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: None

INCOMPATIBILITY: None

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO,

Form: MSDS# 855A

Pg, 2

MATERIAL SAFETY DATA SHEET: ARISTO SUPREME Gym Finish 3/77 | Page 2 of 2

SECTION 6: HEALTH HAZARD DATA

ROUTES OF ENTRY/SIGNS AND SYMPTOMS OF EXPOSURE:

Acute: Contact with eyes or skin may cause irritation. Inhalation of mist or vapor may result in nausea, headache or narcosis. Ingestion may be fatal.

Chronic Effects: None

CARCINOGENS: None as listed under OSHA, IARC or NTP

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None

EMERGENCY AND FIRST AID PROCEDURES: If in eyes: flush with large amounts of clear water for 15 minutes and consult a physician. If on skin: Wash affected areas thoroughly with soap and water. If inhaled, and respiratory effects occur, remove to fresh air. If ingested, DO NOT INDUCE VOMITING. Consult a physician.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL OR LEAK PROCEDURES: Pick up with oil absorbent, sawdust or paint remover

WASTE DISPOSAL METHODS: Landfill in accordance with Federal, State and Local regulations.

HANDLING AND STORAGE: Keep out of reach of children. Keep away from strong oxidizers, sources of heat and open flame. Avoid eye and prolonged skin contact. Avoid prolonged breathing of vapor. Do not cut, weld or puncture container. Observe label precautions when handling containers.

OTHER PRECAUTIONS: Replace lid after use. Do not reuse container.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Respirator meeting NIOSH/MESA 23C specifications.

VENTILATION: Mechanical exhaust is adequate.

GLOVES: Plastic or neoprene EYE PROTECTION: Chemical safety goggles

OTHER PROTECTIVE EQUIPMENT: None

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling. Clean contaminated clothing before reuse.

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

Form: MSDS 0855A