#31832

## U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

## MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

| SECTION I  |                         |  |  |  |  |  |
|--|-------------------------|--|--|--|--|--|
| MANUFACTURER'S NAME  | EMERGENCY TELEPHONE NO. |  |  |  |  |  |
| Rochester Midland  | 716-266-2250            |  |  |  |  |  |
| ADDRESS (Number, Street, City, State, and ZIP Code) 333 Hollenbeck Street, Rochester, NY | 14621                   |  |  |  |  |  |
| CHEMICAL NAME AND SYNONYMS   | TRADE NAME AND SYNONYMS |  |  |  |  |  |
| None .   | Waxoff                  |  |  |  |  |  |
| CHEMICAL FAMILY  | FORMULA                 |  |  |  |  |  |
| Stripper   | Mixture                 |  |  |  |  |  |
|  |                         |  |  |  |  |  |

|   | SECTION           | V 11 | HAZAF          | RDOUS INGREDIENTS                           | ••  |                |
|---|-------------------|------|----------------|---|-----|----------------|
| PAINTS, PRESERVA                                      | TIVES, & SOLVENTS | *    | TLV<br>(Units) | ALLOYS AND METALLIC COATINGS                | ×   | TLV<br>(Units) |
| PIGMENTS  | N.A.              |      |                | BASE METAL N.A.                             |     |                |
| CATALYST  | N.A.              |      |                | ALLOYS N.A.                                 |     |                |
| VEHICLE   | N.A.              |      |                | METALLIC COATINGS N.A.                      |     |                |
| SOLVENTS  | N.A.              |      |                | FILLER METAL PLUS COATING OR CORE FLUX N.A. |     |                |
| ADDITIVES   | N.A.              |      |                | OTHERS N.A.                                 |     |                |
| OTHERS  | N.A.              |      |                |   |     |                |
| HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES |                   |      | *              | TLV<br>(Units)                              |     |                |
| Sodium metasilicate                                   |                   |      | <b>&lt;</b> 5  | 10 mg/14                                    |     |                |
| Ethanolamin   | е                 |      |                |   | < 2 | מסת 3          |
|   |                   |      |                |   |     |                |
|   |                   |      |                |   |     | t              |

| SECTION III - PHYSICAL DATA                   |          |                                    |      |  |  |
|---|----------|------------------------------------|------|--|--|
| BOILING POINT (°F.)                           | 212      | SPECIFIC GRAVITY (H20=1)           | 1.05 |  |  |
| VAPOR PRESSURE (mm Hg.)                       | as water | PERCENT, VOLATILE<br>BY VOLUME (%) | 85   |  |  |
| VAPOR DENSITY (AIR=1)                         | as water | EVAPORATION RATE                   | 1    |  |  |
| SOLUBILITY IN WATER                           | complete |                                    |      |  |  |
| APPEARANCE AND ODOR amber liquid - lemon odor |          |                                    |      |  |  |

| SECTION IV - FIRE AND EXPLOSION HAZARD DATA |                |                  |      |             |   |  |
|---|----------------|------------------|------|-------------|---|--|
| FLASH POINT (Method used)                   | None           | FLAMMABLE LIMITS | N.A. | اما         | Uel                                     |  |
| EXTINGUISHING MEDIA                         | No fire hazard |                  | 1    |             |   |  |
| SPECIAL FIRE FIGHTING PROCEDU               | RES<br>None    |                  |      | <del></del> |   |  |
| •   |                |                  |      |             | - · · · · · · · · · · · · · · · · · · · |  |
| UNUSUAL FIRE AND EXPLOSION H                | AZAROS None ~  | <del></del>      |      | 1           |   |  |
|   |                |                  |      |             |   |  |

PAGE (1) N.A. = Not Applicable

(Continued on reverse side)

X3466 Form OSHA-20



| SECTION V - HEALTH HAZARD DATA  |
|---|
| THRESHOLD LIMIT VALUE   |
| N.A   |
| EFFECTS OF OVEREXPOSURE   |
| Eye: irritation   |
| Possible skin irritant upon prolonged exposure                            |
| EMERGENCY AND FIRST AID PROCEDURES Skin: wash with water. Use hand lotion |
| Eye: rinse with plenty of water.  |
| Ingestion: Give large amounts of water or milk.                           |

| SECTION VI - PEACTIVITY DATA |                                       |                |      |   |  |  |  |
|------------------------------|---------------------------------------|----------------|------|---|--|--|--|
| STABILITY                    | UNS.                                  | TABLE          |      | CONDITIONS TO AVOID                         |  |  |  |
|                              | STA                                   | }              | х    | N.A.  |  |  |  |
| INCOMPATABILI                | TY Mater                              | rals to avoid) | Acid | d solutions precipitate active ingredients. |  |  |  |
| HAZARDOUS DE                 | MAZARDOUS DECOMPOSITION PRODUCTS None |                |      |   |  |  |  |
| HAZARDOUS                    |                                       | MAY OCCUR      | i    | CONDITIONS TO AVOID                         |  |  |  |
| POLYMERIZATIO                | )N                                    | WILL NOT OCCUR |      | X N.A.                                      |  |  |  |
|                              |                                       |                |      |   |  |  |  |

| SECTION VII - SPILL OR LEAK PROCEDURES   |
|--|
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  Small spills: rinse down drain. Large spills: dike to contain. Reclaim as |
| much as possible. Absorb with inert materials. Flush away residue.   |
|  |
| WASTE DISPOSAL METHOD Rinse down drain, or dispose of large quantities in accordance with  |
| Federal, State and local regulations.  |
|  |

|                                     | SECTION VIII - SPECIAL        | PROTECTION INFORMATION                                |
|-------------------------------------|-------------------------------|---|
| RESPIRATORY PI                      | ROTECTION (Specify type) N.A. |   |
| VENTILATION                         | LOCAL EXHAUST                 | SPECIAL   |
| N.A.                                | MECHANICAL (General)          | OTHER   |
| PROTECTIVE GLOVES Rubber or plastic |                               | EYE PROTECTION Goggles to prevent accidental splashes |
| OTHER PROTECT                       | IVE EQUIPMENT N.A.            |   |

| SECTION IX - SPECIAL PRECAUTIONS  PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING  Keep from freezing. |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
| OTHER PRECAUTIONS N.A.   |  |  |  |  |  |
|  |  |  |  |  |  |

PAGE (2)

CONFIDENTIAL

**x3466** 

Form OSHA-20 Rev. May 72