Chemical Family: Mixture Chemical Formula: NA'

Chemical Trade Name, synonyms: NA

and the second of the second

Distributed by: Mueller Sports Medicine, Inc. P.O. Box 99, 1 Quench Drive Prairie Du Sac, WI. 53578

Telephone: 608-643-8530

74-98-6

67-63-0

Prepared by IKI: Derek J. Bemis

Propane

SECTION 2 - INGREDIENTS

CAS REG # NAME

106-97-8 Butane

The state of the s

1000 ppm, OSHA 800 ppm, ACGIH 400 ppm, OSHA

PEL/TLV, SOURCE

71-55-6 * 1,1,1-Trichloroethane 350 ppm, OSHA The percentage of this .ingredient in product ... A manais less than 20%

is 30-50%

* Isopropyl Alcohol

The percentage of this ingredient in product

76-22-2 Synthetic Camphor

2 ppm, ACGIH

2216-51-5 5-Methyl-2(Methylethyl) cyclohexanol

Not established

BankA Undecylenic Acid COLUMN IT (AUTOMOLIC)

of the billion excited a Fluor wine, til bidson i toll gif

All and the first states

不知時天 19 日本 阿斯斯 數數無限分響行

Not known

NOTE: This chemical is subject to the reporting requirements of section 313 of the Emergency Planning and Community Rightto-Know Act of 1986 and of 40 CFR 372.

PAGE 2, MSDS #90178

SECTION 3 - PHYSICAL DATA

Boiling Range: -44 to over 165°F.

Pressure in can at $70^{\circ}F$: Approx. 50 psig Vapor Density (Air = 1): Greater than 1.0

Solubility in water: Moderate

Specific Gravity (Water = 1) of product: Less than 1.0

Percent volatile by weight: approx. 99 %

Evaporation Rate (Butyl Acetate = 1): Greater than 1 Appearance and odor: Cloudy liquid, with alcohol odor.

SECTION 4 - FIRE AND EXPLOSION HAZARDS

Flammability category: Extremely Flammable (Reference - Consumer Product Commission, flame projection test for aerosol products, per 16 CFR 1500.45)
Flash Point, method: -156°F, estimated for propellant Flammable Limits: Estimated 1.9% LEL, 9.5% UEL Extinguishing media: Foam, dry chemical, carbon dioxide.

Unusual fire and explosion hazards: Avoid possible bursting of aerosol can. Do not store where temperature may exceed 120°F. Do not puncture or incinerate.

Special fire fighting procedures: Avoid possible accumulations of vapors at floor level, as vapor is heavier than air. Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

SECTION 5 - HEALTH HAZARD DATA

. :1

Suggested exposure guideline: 350 ppm Primary route of exposure: Inhalation, skin contact

Effects of overexposure - inhalation: Dizziness, nausea, headaches, and loss of consciousness.

Effects of overexposure - skin contact: Irritation upon prolonged contact. Defatting of skin possible with prolonged contact.

Effects of overexposure - eye contact: Irritation.

. 2014

Emergency and first aid procedures - inhalation: Remove to fresh air. Artificial respiration, get medical attention.

Emergency and first aid procedures - skin contact: Flush area well with water. Remove and wash any clothing soaked with product.

Emergency and first aid procedures - eye contact: Flush eyes well with running water for 15 minutes.

Emergency and first aid procedures - ingestion: Call physician or poison control center immediately. Proper treatment is dependent on condition of patient and amount ingested.

PAGE 3, MSDS #90178

ne . re_{g.}

to built par in

÷. (

42 8 . FS

This product contains no known or potential carcinogens as listed per NTP, IARC, or OSHA (29 CFR 1910.1200(D)#4).

and the second of the second Additional health hazard data: Note to physician - Contains chlorinated solvent. Increased cardiac sensitivity and possible arrhythmia may result from overexposure. administer epinephrin or other stimulat following overexposure. 25 34.17 34

SECTION 6 - REACTIVITY DATA

Stability: Stable Conditions to avoid: Heat, sparks, flames, strong oxidizers Hazardous polymerization: Will not occur Hazardous decomposition products: Carbon monoxide, other toxic gases possible if thermally decomposed.

SECTION 7 - SPILL OR LEAK PROCEDURES

1311

tro

Steps to be taken in case material is released or spilled: Ventilate area well. Avoid any sources of ignition for flammable liquid or vapor. Soak up on suitable absorbent material.

Waste disposal method: Conventional solvent waste receptacle. Dispose of in accordance, with all local, state and federal regulations. Avoid contamination of groundwater.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiration protection: If TLV is exceeded wear NIOSH-approved self-contained breathing device or respirator.

Ventilation: Must be adequate to maintain vapors at less than 350 ppm, particularly at floor level as vapors are heavier than

Protective gloves: Neoprene, Polyvinyl Alcohol for prolonged contact.

Eye protection: Safety glasses or goggles recommended.

SECTION 9 - HANDLING AND STORAGE PRECAUTIONS

al to one otherwise, and the

Precautions to be taken in handling and storage: Do not store where temperature may exceed 120°F. Do not store near heat, fire, flame, or sparks.

PAGE 4, MSDS #90178

SECTION 10 - SPECIAL PRECAUTIONS

Precautions for usage: Do not use near heat, fire, flame or sparks. Avoid excessive breathing of vapor. Do not spray in direction of body. Use only in accordance with directions.

Notice: This data represents typical values, not product specifications. No guarantee of accuracy or completeness is made. No responsibility is assumed for any kind of loss or damages arising from use of this data.

ti i japikka tali sekeleb Tipingeleb

CAMBOL BOOK TYPE BELLEVILLE

on filling or record oxiditions of the control oxide.

radilara **vo lament**en etilelarione rati Kal**ini**k, In . sovikor a ras rad**irikasi**ske (ko og 1882)

lei ered**es effici dis**vire in erire Luc er läh **sonde** (Istoik in erire Lati van erire

MORARE WILL OF HE CARA CARLET

have apparance of the skip can be skip with the property of the control of the co

The Hand to the term of the substitution of the term and the term of the control of the term of the control of the term of the control of the term of

of dentity weeper a salyvigy's Alcone for prolone :

. Debamacon radion of the commended.

alion russalas 30.

ကြောင့် တွေကို ကြောင်းသော ကြောင်းသောများ များသော မေးသော မြောင်းသော မေးသည် သည် သည် မေးသည် မြောက်သည်။ မေးသည် မြ ကြောင့် မြောက်ကြောင်း မေးသည် ကြောင်းသည် မြောက်သည်။ မြောက်သည် မေးသည် မေးသည် မြောက်သည် မေးသည် မြောက်သည် မေးသည် မ