[AVI /33

Astro-Valcour, Incorporated

97/801/2 97/2859 SCRATCH-FOAM 97/2868 97/8200 97/2858 5200/00

18 Peck Avenue/P.O. Box 148 Glens Falls, NY 12801

Telephone 518-793-2524 Fax 518-793-2904 Telex 926447

Section 1 name & product		
BAD E DEOQUEE		
(a)	518/793-25	24
street address		
(c) 18 PECK AVENUE	for latest data consult manufacturer	date this information (d) 11/06/90
e) GLENS FALLS, NY 12801		
hemical name, trade name, and synonyms f) STANDARD POLYSTYRENE FOA	AM SHEET	
ormula of primary component(m)		
g) POLYSTYRENE (C,H,)n		
ection 2 ingredients -		
	ITIES BEING WITHHELD AS IONALS PER 29 CFR 1910	.1200(C)
	IONALS PER 29 CFR 1910	.1200(C)
_	IONALS PER 29 CFR 1910	7LV
olystyrene Resin	IONALS PER 29 CFR 1910	TLV (units)
olystyrene Resin -Pentane ucleating Agents	IONALS PER 29 CFR 1910	TLV (unita) None
olystyrene Resin -Pentane ucleating Agents	IONALS PER 29 CFR 1910	TLV (units) None 600 PPM
olystyrene Resin -Pentane ucleating Agents olor Concentrate		TLV (unita) None 600 PPM None
olystyrene Resin -Pentane ucleating Agents olor Concentrate		TLV (unita) None 600 PPM None
olystyrene Resin -Pentane ucleating Agents olor Concentrate Blowing agents are fugitive		TLV (unita) None 600 PPM None
olystyrene Resin -Pentane ucleating Agents olor Concentrate Blowing agents are fugitive	and rapidly leave prod	TLV (unita) None 600 PPM None
olystyrene Resin -Pentane Icleating Agents Olor Concentrate Blowing agents are fugitive Iction 3 physical data Oiling point (F)	and rapidly leave product specification values) N/A 6 specific gravity	TLV (units) None 600 PPM None None None luct after manufacture.
olystyrene Resin -Pentane ucleating Agents blor Concentrate Blowing agents are fugitive ection 3 physical data colling point (F) apor pressure (mmHgst 20 c)	and rapidly leave product specification values) N/A 6 specific gravity N/A 7 3 volatile by volu	Vunita) None 600 PPM None None None None 0.03-0.04
olystyrene Resin -Pentane ucleating Agents clor Concentrate Blowing agents are fugitive ection 3 physical data coiling point (F) apor pressure (mmHgat 20 c) apor density (air-1) clubility in water Incolu	and rapidly leave product specification values) N/A 6 specific gravity N/A 7 % volatile by volu	(unita) None 600 PPM None None None None 0.03-0.04 Est. < 5%
olystyrene Resin -Pentane ucleating Agents olor Concentrate Blowing agents are fugitive ection 3 physical data poiling point (F) rapor pressure (mmHgat 20 c) rapor density (air-1) clubility in water Insolu	and rapidly leave product specification values) N/A 6 specific gravity N/A 7 % volatile by volu	Units) None 600 PPM None None None None Luct after manufacture. 0.03-0.04 Est. < 5% Varies, none
olystyrene Resin -Pentane ucleating Agents clor Concentrate Blowing agents are fugitive ection 3 physical data coiling point (r) apor pressure (mmHgat 20 c) apor density (air-1) clubility in water Insolu	and rapidly leave product specification values) N/A 6 specific gravity N/A 7 % volatile by volu N/A 6 color and oder ble 9 physical state	O.03-0.04 Est. < 5% Varies, none foamed plastic
olystyrene Resin -Pentane ucleating Agents clor Concentrate Blowing agents are fugitive ection 3 physical data ciling point (F) apor pressure (mmHgat 20 C) apor density (air-1) clubility in water Insolu Ction 4 fire and explosion hazard data flash point (and method used) N/A	and rapidly leave product approximation values) N/A 6 specific gravity N/A 7 % volatile by volue N/A 8 color and oder Dle 9 physical stato	Units) None 600 PPM None None None None Luct after manufacture. 0.03-0.04 Est. < 5% Varies, none foamed plastic
olystyrene Resin -Pentane ucleating Agents clor Concentrate Blowing agents are fugitive ection 3 physical data coiling point (r) apor pressure (mmHgat 20 c) apor density (air-1) clubility in water Insolu Ction 4 fire and explosion hazard data flash point (and method used) N/A extinguishing X water X foam	and rapidly leave product specification values) N/A 6 specific gravity N/A 7 % volatile by volue N/A 8 color and oder ble 9 physical state 11 flammable limits L.F.L. N/A	U.F.L. N/A
olystyrene Resin -Pentane ucleating Agents clor Concentrate Blowing agents are fugitive ection 3 physical data ciling point (F) apor pressure (mmHqat 20 C) apor density (air-1) clubility in water Insolu Ction 4 fire and explosion hazard data flash point (and method used) N/A extinguishing X water X foam media:	and rapidly leave product product specification values) N/A 6 specific gravity N/A 7 t volatile by volue N/A 8 color and oder ble 9 physical state 11 flammable limits L.F.L. N/A	U.F.L. N/A Vone O.03-0.04 Est. < 5% Varies, none foamed plastic O.F.L. N/A X dry Vother
olystyrene Resin Pentane ucleating Agents clor Concentrate Blowing agents are fugitive Ection 3 physical data coiling point (F) sapor pressure (mmHqst 20 C) sapor density (air-1) clubility in water Insolu cction 4 fire and explosion hazard data flash point (and method used) N/A extinguishing X water X foam media: fog special fire fighting protective equipment	and rapidly leave product of specification values) N/A 6 specific gravity N/A 7 t volatile by volue N/A 8 color and oder ble 9 physical state 11 flammable limits L.F.L. N/A alcohol X co ₂ foam	U.F.L. N/A Vone (unita) None (unita) None 600 PPM None None None 10ct after manufacture.
olystyrene Resin -Pentane ucleating Agents olor Concentrate Blowing agents are fugitive Ection 3 physical data poiling point (F) Rapor pressure (MBHqat 20 C) Rapor density (air-1) Folubility in water Insolution Ection 4 fire and explosion hazard data flash point (and method used) N/A Extinguishing X water X foam Media: foq Special fire fighting protective equipment	and rapidly leave product of specification values) N/A 6 specific gravity N/A 7 t volatile by volue N/A 8 color and oder ble 9 physical state 11 flammable limits L.F.L. N/A alcohol X co ₂ foam	(unita) None 600 PPM None None None None Uct after manufacture. 0.03-0.04 Est. < 5% Varies, none foamed plastic (STP) U.F.L. N/A X dry other



MATERIAL SAFET	Y DATA SI	HEET (pa	age 2)				
15 stability	normal conditions fire conditions	16 con	ditions to avoid STABL	Ξ			
17 incompatibility	vater	ecid	bese	corrosive)	K oxidising materi	.01
materials to avoid other 18 hazardous decomposition p	eroducta -						
INCOMPLETE C DANGEROUS PRO	OMBUSTION DUCTS	COULD	GENERATE	CARBON MONO	XIDE & C	OTHER POTEN	TIALLY
19 hezerdous polymerisation	will occur	not	x		30 co	nditions to avoid N/A	
Section 6 bealth h	stard data		· · · · · · · · · · · · · · · · · · ·				
UNLIKELY DUE 22 eye contact - SOLID OR DUS' 23 skin contact - ESSENTIALLY 1	r could c	AUSE IR					ASION
24 skin absorption =		ATTING					
UNLIKELY DUE			TE				
IF DUST CREAT			SANCE DUS	T ,			
6 effects of overexposure "	-	-	T			· · · · · · · · · · · · · · · · · · ·	····
NONE EXPECTED	UNDER C	ONDITION	NS OF NOR	MAL USE			
7 first aid procedures -							
FOLLOW NORMAI	FIRST A	ID PROC	EDURES SU	CH AS THOSE	RECOMME	NDED BY THE	E RED





Section 7	spill or leak procedures n case material is released or spilled -	
	HANDLE AS INERT MATERIAL	
29 disposal method		
		
FEDERAL &	AS WOULD ANY BASICALLY INERT MATERIAL, IN ACCORDANCE WIT	TH STATE,
Section 8	special protection information	
30 ventilation	local exhaust - RECOMMENDED IF DUST CREATED	
OVER THI	FDMAI CHEMPTANA	*pecia;
RESIDUAL.	ERMAL CUTTING OPERATIONS & TO CONTROL POTENTIAL FUGITIVE BLOWING AGENT FROM CUTTING & GRINDING OPERATIONS	_
	- DIGITIONS.	RELEASE O
	mechanical (general) - RECOMMENDED IN CONFINED	
		other
11 respiratory protect	BUILDUP OF BLOWING AGENT	
protective clothing		
NONE REQU	IRED	
3 eye	not normally necessary X safety glasses without side shields	
	safety glasses with side shields	
	chemical workers goggles	
other protective equi	gas tight poggles or equivalent other	
NONE REQUI	[RED	
ection o		
Precentions to be said	cial precautions or other comments	
	ken in handling and storing	
THIS PRODUCTION WE	CT MAY CONTAIN TRACES OF FLAMMABLE BLOWING AGENT AND SHO ELL VENTILATED AREAS TO PREVENT BUILDUP OF FLAMMABLE VAI TR HUMIDITY CONTROL TO MAINTAIN RELATIVE HIMIDIAN	III.D pp
SO COMETEN	R HUMIDITY CONTROL TO MAINTAIN RELATIVE HUMIDITY ABOVE 4	PORS.
	MO W GRINDING OPERATIONS.	0.5
NEAR CUTTII		
NEAR CUTTII		

Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

crayon

Required under USDL Safety and Health Regulations for Ship Repairing, Shiphuilding, and Shiphreaking (29 CFR 1915, 1916, 1917)

		SECT	ION I			
MANUFACTURER			E	MERGENCY TELEPHO	NE NO.	
<u> </u>		-		717-454-3596		
CHEMICAL NAME AND SYNONYMS MIXTURE CHEMICAL FAMILY MIXTURE	**************************************		CRAYON CRAYON			
MIXIURE			CRAYON	MIX		
SECTION	J 11 -	HAZAF	RDOUS INGREDIEN	ITS NONE		
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND ME	TALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL			V= 10 447
CATALYST			ALLOYS			
VEHICLE			METALLIC COATINGS			
SOLVENTS			FILLER METAL PLUS COATING OR CO	RE FLUX		
ADDITIVES			OTHERS			
OTHERS						
HAZARDOUS MIXTURE	SOF	OTHER LIC	DUIDS, SOLIDS, OR GASE		%	TLV (Units)
NON-TOXIC						(Olits)
AVILLA VILLA					+-	
						
	······					
SEC	TIOI	VIII - P	HYSICAL DATA			
BOILING POINT (°F.)			SPECIFIC GRAVITY (H2	O=1)	1	7
VAPOR PRESSURE (mm Hg.)			PERCENT, VOLATILE BY VOLUME (%)		_	
VAPOR DENSITY (AIR=1)			EVAPORATION RATE			
SOLUBILITY IN WATER negligible					1	
APPEARANCE AND ODOR Various colors. Essentially none						
0507101						
SECTION IV -	FIRI	E AND E	XPLOSION HAZAP			
N/A			FLAMMABLE LIMIT	S Lei		Uei
extinguishing media carbon dioxide, sand, or foam						
SPECIAL FIRE FIGHTING PROCEDURES ha	nd1e	the sa	ame as any fire			
UNUSUAL FIRE AND EXPLOSION HAZARDS do not store with strong oxidizers						

PAGE (1)

(Continued on reverse side)

Form OSHA-20 Rev. May 72

THRESHOLD LIM	EL MALUE	SECTION	V - HEA	ALTH HAZARD DATA NON-TOXIC
EFFECTS OF OVE			arabi aga ir igrova esti	
	FIRST AID PROCE			
remaining is additional to the control of the contr				
		SECTIO	ON VI · I	REACTIVITY DATA
STABILITY	UNSTABLE		CONDITIO	DNS TO AVOID
STABLE X				
	Y (Materials to avoid	S	olvents	will dissolve
	composition PRO conoxide in ca		ncomplet	e combustion
HAZARDOUS POLYMERIZATIO	MAY OC	CUR		
	VILL NO	T OCCUR	X	
	SE	CTION VI	ı - SPILl	OR LEAK PROCEDURES
STEPS TO BE TAK	KEN IN CASE MATE			
D HOOVED	DDEE DRADUCT			
RECOVER-	FREE PRODUCT			
WASTE DISPOSAL	_ METHOD			
DISPOSE	OF ACCORDING	TO LOCA	L REGULA	TIONS
	SECTIO	2012/111	SPECIAL	PROTECTION INFORMATION
RESPIRATORY P	ROTECTION (Speci)			
VENTILATION	LOCAL EXHAL	Jst	NONE	SPECIAL
	MECHANICAL	(General)		OTHER
NONE PROTECTIVE GL	OVES NONE			EVE PROTECTION SAFETY GLASSES
OTHER PROTECT	TIVE EQUIPMENT	NONE		
		,		
DDEGALITICALS =	O OF TAKEN IN IN			PECIAL PRECAUTIONS
	O BE TAKEN IN HA			3
STORE IN	COOL, DRY P	LACE		
OTHER PRECAU				

PAGE (2)

Form OSHA-20 Rev. May 72



DIVISION BIENS DE CONSOMMATION DU GROUPE BUREAU VERITAS

TOTAL CADMIUM ANALYSES

Date:

March 20, 2000

Recipient:

Mrs. SHANA'A ZOGHEIB

Company:

ACLA - Sari 2 Rue Ampère Address: 94200 IVRY SUR SEINE

FRANCE

Sample ID:

Multicolor board

Page:

Report No.: Date received:

TO:

Reference No.: Supplier:

Origin: Material(s): 1 011

(5400)012-0006 January 12, 2000

Not Available Scratch-Art Co.

United States

Paint Coatings / Paper / Cardboard

RESULTS:

SAMPLE B Black coating

C Yellow coating D Blue coating

E Red coating

LT= Less Than

RESULT

LT 5 LT 5 LT 5

LT 5

Results are reported as milligrams per kilogram (mg/kg)(ppm)

Limit: 100 mg/kg

PASS / FAIL

PASS PASS PASS PASS

The sample COMPLIES with the requirements of the Council Directive 91/338/EEC dated June 18, 1991 and with the CONCLUSION: requirements of "TITLE II: CADMIUM AND ITS COMPOUNDS" of the French Decree No. 94-647 dated July 27, 1994 related to the limitation on the marketing and the use of cadmium and of their compounds.

ACTS TESTING LABS

Dominique Billeret, R & D Manager

ACTS Laboratoire d'Essais, SARI. Les l'eupliers, 17 rue du Verruquer 59960 Neuville en Ferrain, France www.actsrcsting.com

Not reproduce dealing it was concern that while I however are continued and grain desirable and a concern that while I however are continued and a concern that we is a concern to provide and in the concern to provide and in the concern that the

SARL au capital de 50 1100 F - RCS Roubaix Tourcoing B 380 226 795

1