8779387795 Pg.1

SARA TITLE III SECTION 313 AND 40 CFR Part 372 TOXIC CHEMICAL NOTIFICATION SHEET

ELMER'S CARPENTERS WOOD GLUE

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.

CAS Registry

Number Chemical Name

Pot. By Weight

None required per SARA TITLE III SECTION 313

This Toxic Chemical Notification Sheet must not be detached from the Material Safety Data Sheet (MSDS). Any copying and redistribution of the MSDS shall include copying and redistribution of this notification sheet attached to copies of the MSDS subsequently redistributed.

STATE OF THE STATE

060 E700

PRINT DATE: 23-May-91 01:55 PM

DISCLAIMER

1. Figure 11. 2 WARRANTS FRESTOR 12 WITH 1 1. 1. 18 PM. 18 PM. 1. 18 PM. 1



MATERIAL SAFETY DATA SHEET

#020460

Burden Inc.

en a jerran Pari a visto (* 11. m.)

1.400

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT THE INFORMATION CONTAINED ON THESE SHEETS BE MADE AVAILABLE TO YOUR WORKER. INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY.

ATTN: SAFETY DIRECTOR NON-EMERGENCY TELEPHONE 800-848-9400(MSDS,ORDERS)

614-431-6680 (TECH. INFO)

DESCRIPTION: ELMER'S CARPENTERS WOOD GLUE

PAGE PRODUCT TYPE: PVAC BASED ADHESIVE CUR ISS 05-DEC-90

APPLICATION: E614, E700, E701, E702, E704, E705, E706, E970.

SIGNAL WORD

This material is not a "health hazard" or a "physical hazard" as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29 CFR Part 1910.1200 "Hazard Communication" Standard.

CHEMICAL HAZARD RATING

HEALTH=1(slight)

FIRE=Q(least)

REACTIVITY=Q(least)

29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS

CAS/REGISTRY NO. MATERIAL DESCRIPTION % RANGE

None known to Borden.

PHYSICAL DATA

PERCENT VOLATILES 54.5 4.8 pH AT 25 C

SPECIFIC GRAVITY 1.1

APPEARANCE LIGHT YELLOW LIQUID

AUTOIGNITION TEMPERATURE NOT AVAILABLE BOILING POINT 100 DEGREES C

VAPOR DENSITY (AIR=1) < 1

VAPOR PRESSURE, MM HG @ 20 DEG C 17.5 EVAPORATION RATE (BUTYL ACETATE=1) < 1

UP/LOW FLAMMABLE LIMITS NOT APPLICABLE FLASH FOINT NOT APPLICABLE

FREEZING POINT O DEGREES C

MILD ACETIC AROMA ODOE:

ODOR THRESHOLD, PPM NOT AVAILABLE SOLUBILITY IN WATER DISPERSIBLE MOC CALCULATED NEGLIGIBLE

COEFFICIENT OF WATER/OIL DISTRIB. NOT AVAILABLE

READ NEXT PAGE

on descriptions of the second of the second

MATERIAL SAFETY DATA SHEET 8793- 8

Enden for

" -- 21, -- 1 -- 1 -- 1 -- 1 -- 1 -- 1

THE BACK OF THE STORY

DESCRIPTION: ELMER'S CARPENTERS WOOD GLUE

PAGE

PRODUCT TYPE: PVAC BASED ADHESIVE

CUR ISS 05-DEC-90

APPLICATION: E614, E700, E701, E702, E704, E705, E706, E970.

IMMEDIATE HEALTH HAZARD DATA

SKIN ABSORPTION: Not toxic dermally when tested as described in 16 CFR Part 1500.3 (c) (1) and (2).

INGESTION: Not toxic orally when tested as described in

16 CFR Part 1500.3 (c) (1) and (2).

INHALATION: Not toxic by inhalation when tested as described in 16 CFR Part 1500.3 (c) (1) and (2). SKIN: May cause irritation on prolonged or repeated Not a primary irritant (primary skin irritation index less than 5.0/8.0) when tested as

described in 16 CFR Part 1500.41.

EYES: Not an irritant when tested as described in 16 CFR Part 1500.42.

HANDLING PRECAUTIONS

SKIN: Persons with sensitive skin should avoid prolonged, continuous contact with skin. If irritation develops, discontinue use. Handle in accordance with good industrial hygiene and

safety practices.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: If accidently swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions. SKIN CONTACT: In case of irritation, flush with

EYE CONTACT: Immediately flush eyes with plenty of water. Call a physician if irritation persists.

FIRE AND EXPLOSION HAZARD DATA

Will not burn unless water has evaporated.

In case of fire, water should be used to keep fireexposed containers cool.

REACTIVITY DATA

Normally stable as defined in NFPA 704-12(4-3.1).

Hazardous polymerization:

Will not occur.

Incompatibilities:

Strong acids and alkaline materials.

Other Hazards:

None known to Borden.

Decomposition products may include:

CO, CO2.

MATERIAL SAFETY DATA SHEET 87793

611 471 6600

Burden bus

The equation of the second

ranga no caron or only of Mhill or

DESCRIPTION: ELMER'S CARPENTERS WOOD GLUE PAGE CUR ISS 05-DEC-90

PRODUCT TYPE: PVAC BASED ADHESIVE

APPLICATION: E614, E700, E701, E702, E704, E705, E706, E970.

CONTROL MEASURES

No special control measures necessary under normal

conditions of use.

PERSONAL PROTECTION INFORMATION

No special protection necessary.

SPILL OR LEAK PROCEDURES

Soak up with absorbent material and remove to a

chemical disposal area.

Prevent entry into natural bodies of water.

WASTE DISPOSAL

E STEET TO THE SECTION OF THE STEET STEET

Recover free liquid. Absorb residue and dispose of

according to local, state/provincial, and federal

requirements.

STORAGE PRECAUTIONS

Keep from freezing.

Store in a cool, dry place.

Keep containers tightly closed.

DOT CLASSIFICATION

Not Regulated.

PREVIOUS ISSUE:13-NOV-90 CURRENT ISSUE:05-DEC-90

PRINT DATE: 23-May-91 01:55 PM

THIS IS THE LAST PAGE