Canon

MATERIAL SAFETY DATA SHEET

Canon U.S.A., Inc. One Canon Plaza

Lake Success, NY 11042 Telephone: 516-488-6700

24 hr. Emergency Contact CHEMTREC: 800-424-9300

Date of preparation: 11/85
Date of revision: 11/91

SECTION 1 PRODUCT IDENTIFICATION

TRADE NAME:

NP-120/125 Toner

PRODUCT DESCRIPTION:

Toner powder for Canon copiers (200g)

ITEM NO:

F41-1351-100

NFPA HMIS RATINGS:

Health: 0, Flamma

Flammability: 1, Reactivity: 1

SECTION 2 INGREDIENTS

(Toner)

<pre>Principal Component(s)</pre>	CAS No.	WT. %	OSHA (PEL) ACGIH (TLV)
Polyolefin Wax		50-60	N/A
Iron Oxide	1317-61-9	40-50	N/A
Amorphous Silica	7631-86-9	5-10	10mg/m3(TWA)
Cerium Oxide	68909-13-7		N/A
Salicylic Acid			
Chromium(III) Chelate	72869-85-3	1-4	(See Section 5A-5C)

Manufacturer contact states all other information proprietary.

N/A = Not Applicable

Concerning carcinogenicity, the ingredients listed above are not listed on the latest NTP Annual Report, IARC Monographs and OSHA regulations.

N/A.

N/A.

SECTION 3 PHYSICAL DATA

APPEARANCE AND ODOR: Fine powder, slight plastic odor

BOILING POINT (C):

MELTING POINT: N/A.
VAPOR PRESSURE (mmHg.): Negligible.

VAPOR DENSITY (AIR=1):

SOLUBILITY IN WATER: Negligible.

SPECIFIC GRAVITY (Water=1): N/A

PERCENT VOLATILE BY VOLUME: Negligible. EVAPORATION RATE (BUTYL ACETATE= 1): Negligible.

PH IN CONCENTRATE:

PH IN CONCENTRATE:
PH IN DILUTION AS USED:

Cannot be determined.

Cannot be determined.

Canon

94594, 94585 MSDS#: CPY-0157-001 (2/3)

SECTION 4 FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:

N/A

EXTINGUISHING MEDIA:

Water, Dry Chemical, CO2

SPECIAL FIRE FIGHTING PROCEDURES:

None UNUSUAL FIRE AND EXPLOSION HAZARDS: This material, like most organic

materials in powder form, is capable of

creating a dust explosion. Refer to NFPA

Pamphlet No. 654, "Standard for the Prevention Fire and Dust Explosions in the Chemical, Dye Pharmaceutical and Plastics Industries, " if this material is to bereduced or collected

as a powder.

SECTION 5 HEALTH HAZARD DATA

Α. EXPOSURE LIMITS: See Section 2

Chromium (III) Compounds as Chromium = 0.5mg/m3 (OSHA TWA)

OSHA (TWA/PEL):

15mg/m3 (Total Dust)

5mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV):

10mg/m3 (Total Dust)

EFFECTS OF OVEREXPOSURE: В.

Minimal respiratory tract irritation may

occur as with exposure to large amounts

any non-toxic dust.

There are no known health hazards, mutagenicity, carcinogenicity or

teratogenicity.

C. TOXICITY DATA:

Test Mutagenicity

Species S. Typhimurium

Results Negative

SECTION 6 EMERGENCY FIRST AID PROCEDURES

Inhalation:

Remove from exposure to fresh air.

Eye Contact:

Open eye and flush with plenty of water.

irritation persists get medical attention.

Skin Contact:

Wash with soap and water.

Ingestion:

Drink several glasses of water. Call a physician.

SECTION 7 REACTIVITY DATA

STABILITY:

Stable.

INCOMPATIBILITY:

Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: As with any other organic material,

decomposition will produce Carbon

Dioxide and Carbon Monoxide.

HAZARDOUS POLYMERIZATION:

Will not occur.

Canon

94585,94594

MSDS#: CPY-0157-001 (3/ 3)

SECTION 8 SPILL, LEAK AND DISPOSAL PROCEDURES

SPILLS AND LEAKS:

Sweep material onto paper and place in a fiber carton

DISPOSAL METHOD:

No special disposal technique required. Ensure

compliance with federal, state and/or local

regulations.

SECTION 9 SPECIAL PROTECTION INFORMATION

VENTILATION:

Good general ventilation should be

sufficient.

PROTECTIVE GLOVES: EYE PROTECTION:

None required. None required.

OTHER PROTECTIVE EQUIPMENT:

None.

SECTION 10 SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep out of réach of children.

Keep from contact with oxidizing materials.

SECTION 11 REGULATORY INFORMATION

CHEMICALS REQUIRED TO BE REPORTED UNDER SARA TITLE III, CERCLA:

Chromium and compound:

2.0 Wt% (maximum)

{As chromium metal: 0.5

0.5 Wt% (maximum)}

ALL COMPONENTS ARE REGISTERED IN ACCORDANCE WITH TSCA.

DEPARTMENT OF TRANSPORTATION

Proper Shipping Name: N/A

Hazard Class: N/A

UN ID No.: N/A

This information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process.